

PROTERO GRILLE OPEN CELL





PHYSICAL DATA

Material substrates - Aluminum | Extruded

Thickness .125"

- Fire Performance Class A: Tested per ASTM E84. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. CAN/ULC S102 surface burning characteristics. Flame Spread Rating 25 or less. Smoke Developed Classification 50 or less.
- Weight depends on cell configuration (1.2 1.8 lbs/sq ft)
- Warranty One Year Limited
- Surface Finish Factory-applied polyester paint. Available in Standard Colors and Color Matched.
- Seismic areas Protero has been engineered for use in all seismic areas. Installations may require additional attachment from panel to suspension bar. Check with local code officials or a licensed engineer for additional requirements.

SUSTAINABILITY

CONTRIBUTES TO LEED® POINTS -

- LEED BD+C: New Construction v4
- MR: Regional Materials
- MR: Recycled Content
- LEED ID+C: Commercial Interiors v4
 EQ: Low-Emitting Material
- No VOC'S: No added urea-formaldehyde
- EPD 'Environmental Product Declaration'
- EPD 'Environmental Product Declaration' for raw material components
- Recycled Content up to 80%
- LEED® is a registered trademark of the U.S. Green Building Council

FEATURES

- Open structure design enhances visual depth and promotes airflow for a sleek, industrial look.
- High open area percentage (over 70%) is available when required in sprinklered areas to allow unobstructed water flow.
- Attaches to 15/16" HD Grid or custom suspension system.
- Standard panel sizes
- ▶ 2' x 2' panel
- ▶ 2' x 4' panel
- Grille configurations are available in rectangular and square formats. Standard cell sizes are listed below, custom sizes are available:
- ▶ W/L: 4" x 6", 4" x 8", 6" x 6", 6" x 8", 8" x 6", 8" x 8", 12" x 6"
- Torsion spring design allows for easy plenum access.
 Panels can remain hinged to suspension to avoid damage.
- Cleanable using CDC recommended and EPA-approved disinfectants for fog, spray & wipe.
- Optional utility troughs discreetly house MEP systems while ensuring easy access for maintenance.
- Designed for exact fit no site cutting required.



STANDARD COLORS

Maxxit powder coat finishes offer superior chemical, scratch and UV resistance, they do not emit VOC's and are available in a broad range of textures, glosses and specialty looks.




Grey (65-75 Gloss)





M

PROTERO DESIGNS





DESIGN REALIZED

From the familiar to the truly one of a kind, Maxxit brings your design vision to life. With ceilings and walls crafted from Wood, Felt, Metal, Composites & more there is no limit to what we can create together.











